

618 MSP *e* Machine Specifications and Dimensions:

Force Range	900 lbs. (4Kn) to 12,000lbs. (53Kn)
Repeatability	+/- 2% of force setting
Throat Depth	18" (457mm)
Stroke Length	0 to 8.0" (0 to 200mm)
Adjustable up stroke	3/8" – 6" (10 – 150mm)
Oil Tank Reservoir	10 gallons (39 liters)
Motor	2 HP
Electrical	200v to 575v 3 phase 50 or 60hz.
Foot print dimensions	(LxWxH)) 1143mm x 467mm x 2336mm (44" x 34" x 92")
Fastener Range	M2 to M10
Clinching Capability	1mm to 6mm combined thickness

For more information on the 618MSPe and other Haeger products, visit our website at www.haeger.com or contact your authorized Haeger distributor.

Always the most cost effective solution
for your fastener insertion challenge!



Safe, Dependable, Versatile,
Affordable ... Haeger !

618

MSP *e*

Fastener
Insertion
System



Haeger USA
Manufacturing Headquarters
811 Wakefield Drive
Oakdale, CA 842511
United States
T +1 209 848 4000

Haeger Europe
Textielstraat 18b
7575 CA Oldenzaal
The Netherlands
T +31 541 530 230

Haeger Asia
99 Middle Chenfeng Road
Kunshan
Jiangsu Province, China
215300
T +86 512 5726 9300

Haeger
a PennEngineering® Company

Website: www.haeger.com www.pemnet.com E-mail: info@haeger.com



Haeger
a PennEngineering® Company

A: 618MSP *e*

6 ton (53Kn) ram force and 18 inch (457mm) throat depth with adjustable ram retract position. Reliability/energy efficiency of a fully hydraulic machine. Equipped with Haeger's patented safety system. **NEW** features added to the standard equipment: Tooling Protection System and Batch Counter.

B: Positive Stop System (Optional)

The Positive Stop System provides an easily adjustable method of precisely maintaining the stopping point of the machine cylinder. The system is particularly well suited for improving uniformity on soft, delicate work pieces. It is also effective when inserting small hardware. In addition to aluminum, the system also provides excellent insertion results on a wide variety of softer materials such as fiberglass, printed circuit boards, and many plastic or composite materials.

C: MAS 350 Modular Autofeed System (Optional)

The Modular Autofeed System can feed nuts, studs and standoffs in the size M2 till M10. The maximum length of the studs and standoffs is 30mm.

D: Built-in TPS Controls


The Tooling Protection System (TPS) is designed to protect both the tooling and the workpiece from damage.

E: Tooling rack

Quick and easy access to tooling.

F: Turret Insertion System (Optional)

Install up to 4 different fasteners in 1 Single Part Handling. (Option includes required Software for Single Part Handling Programming)



Multi-Shuttle Tooling Platform for Nuts, Studs and Standoffs.

The Multi-Shuttle Platform provides a universal quick and easy tool change over between nuts, studs and standoffs – enabling 2-minute total tool changes without realignment. Changeover between Manual and Automatic Tooling setup is faster and easier.




AUTOMATIC BOTTOM FEED TOOLING (ABFT)

for inserting nuts into flat parts as well as into hard-to-reach holes. Such as those on the underside of a flange.



Automatic Bottom Feed J-Frame is used for those difficult to reach flanges



Manual Tooling J-Frame is used for small boxes and short reverse flanges



C

NEW



Single Station settings:

Operators can set the Force, Dwell and Up Travel from this single station screen.



Multi-Station:

Multi-Station is an option that allows the operator to insert more than one fastener in a program. Each station can be configured to have its own individual Force, Dwell Time and Up Travel.



Programs:

Up to 999 programs can be stored



MAS Control Screen:

Operators can turn on and off the auto feed and set eject time and vibration from this screen.